

Advantages

1. Heavier duty, high visibility unit at 4000kg capacity.
2. Unique and simple method of rotation using hydraulic cylinders.
3. Low maintenance.
4. 200 degrees total rotation. Choice of left or right tip (left as standard) 20 degrees anti-clockwise rotation facility.
5. Pre-set speed with controlled and gentle action.
6. Side arm fitted with adjustable box support and top arm fitted with movable extension as standard, lifting eye and bracket to hold hydraulic pipes when not in use.
7. Ideal for the heaviest of user and larger produce boxes as well as the heavy recycling industry.
8. For the larger 8' wide Onion boxes, the Contractor Plus is more suitable.
9. Contractor Plus has a wider carriage and longer pallet forks to support larger boxes and loads.
10. Larger diameter centre shaft for higher loads.

Contact Us

Office hours: Monday to Friday 9am - 5pm.

TEL: 01377 259140

FAX: 01377 259141

Email: sales@agriweld.co.uk

Website: www.agriweld.co.uk

Visit Us

We are situated on the A166 between York and Driffield.



Main Street, Garton on the Wolds,
Driffield, East Yorkshire, YO25 3ET

AGRI WELD



Contractor CE & Contractor Plus Box Rotator

www.agriweld.co.uk

Contractor ^{CE} & Contractor Plus Box Rotator

Intended for contractors, large scale growers and processing/packaging plants this 4-tonne capacity unit will fit forklifts or loaders of 3 tonne and over and is fully adjustable to take any box size.

Contacter with hydraulic clamping lid option



Main pivot and top arm height adjustment



Standard bolt-on bracketing system to fit forklift / loader included

A Tip
For The
Future

Specifications

	Contractor	Contractor Plus
Capacity	4000kg	
Weight (excluding lid and bracketing)	750kg	825kg
Carriage	Class 3 1500mm x 407mm 40mm grade 50D	Class 3 1800mm x 407mm 40mm grade 50D
Forks	100 x 50 x 1200 Class 3b	100 x 50 x 1800 Class 3b
Back Plate	40mm grade 50D	
Rotation	2 double acting hydraulic cylinders and associated fittings and radius arm pivoting on large diameter centre shaft with full length PB1 bush	
Bracketing	Standard bolt-on to fit all applications	
Lid	Optional hydraulic clamping lid available requires 12V electric supply	



View the Operator Manual on our website



View a video of the Quickshift in action on our website